士林電機 Shihlin Electric

EV AC Charger

Specification				
Model		~~ATLTE1-80AAS~~	ATLTE1-50AAS	ATLTE1-32AAS
Type		Wall Mount / With Stand		
Input	Voltage	200~240VAC, Single Phase, L+PE+N		
	Frequency	50/60Hz		
	Current	80A	50A	32A
Output	Voltage	200VAC~240VAC		
	Frequency	80A	50A	32A
	Connector	SAE J1772 (80A)	SAE J1772 (50A)	SAE J1772 (32A)
User Interface	Display	2.89”OLED		
	Push Buttons	Emergency Stop		
	User Authentication	OCPP 1.6J (up to 2.0) / RFID(standard) / APP(optional with MSP)		
Network Connection		Ethernet		
Environmental	Operating Temp.	-30°C ~ +50°C		
	Storage Temp.	-30°C ~ +70°C		
	Humidity	< 95% (Non-condensing)		
	Altitude	< 2000m / < 6561ft		
	Ingress Protection	IP55 / NEMA TYPE 3R		
	Enclosure Protection	IK10		
	Cooling	Natural Cooling		
Mechanical	Dimension (W x D x H)	285mm x 190mm x 412mm / 11.2in x 7.5in x 16.2in		
	Weight	< 6kg / 13.25lb (without plug)		
	Cable Length	5m / 16ft		
Protection		Over voltage/Under voltage/Over current/Surge/ Residual current/Ground fault/Over temperature		
Certification		UL2594 / CSA C22.2 NO. 280:22 UL2231-1 / CSA C22.2 No. 281.1-12 UL2231-2/ CSA C22.2 No. 281.2-12		
		FCC part 15B		